mittently operated local exhaust fans shall be rated at maximum of 3.0 sone. rotely located air-moving equipment (mounted outside of habitable spaces) need meet sound requirements if at least 4 feet of ductwork between fan and intake grill. Exterior landings, decks, balconies, and stairs. Such elements shall be positively anchored to the primary structure to resist both vertical and lateral forces or shall be designed to be self-supporting. Attachment shall not be accomplished by use of toens or malls subject to withdrawal. (GRC R311.5) Firebocking, Firebocking shall be provided in the following locations (CRC R302.11 and CRC R1003.19): Roof diaphragm at ridges. Minimum 2-Inch nominal blocking required for roof diaphragm nailing at ridges. Roof dlaphragm under fill framing. Roof plywood shall be continuous fill framing. Structural steel. Steel used as structural shapes such as wide-flange sections, channels, plates, and angles shall compty with ASTM A36. Pipe columns shall compty with ASTM A500, Grade B. a. Identify the construction and demallion waste materials to be diverted from disposal by recycling, reuse on the project or subage for future use or sale. b. Specify if construction and demallion waste materials will be sorted on-site (source-separated) or bulk mixed (single stream) c. Identify develon facilities where the construction and demallion waste materials will be taken d. Identify construction methods employed to reduce the amount of construction and demallion waste generated o. Specify that the amount of construction and demallion waste materials diverted shall be calculated by weight or cyclinn, but not by only 7. Operation and maintenance manual. First to final inspection, a manual, compact disc. we besend the former, or other acceptable media which includes all of the following shall be placed in the building (CAL Green 4.410.1):

FloorScore program
 Method for the Testing and or Sources Using known as Specification

nguard Children &

THESE ARE MINIMUM REQUIREMENTS AND SHALL NOT SUPERSEDE MORE RESTRICTIVE SPECIFICATIONS ON THE PLANS OR AS REQUIRED BY APPLICABLE CODE.

CS-1

Sheet Number

Edges (Inches)

County of San Diego, Planning & Development Services MINIMUM CONSTRUCTION SPECIFICATIONS

BUILDING DIVISION

equipment during age on the construct

BUILDING RECORD ID:

OWNER OR CONTRACTOR SIGNATURE:

TABLE R602.3(1)
FASTENER SCHEDULE FOR STRUCTURAL MEMBERS
MATERIAL MEMBERS

ccording to ANSI/ACCA 1 Manual D 2009, ASHRAE ralent design software or methods

for landscaping shall per minute at 60 psi

shall be ENERGY STAR compliant and ducted to terminate outsit